

**VKYP.EX15538****Special System Water Control Valve and Clean Agent Extinguishing System Unit Assemblies**[Page Bottom](#)

Special System Water Control Valve and Clean Agent Extinguishing System Unit Assemblies

[See General Information for Special System Water Control Valve and Clean Agent Extinguishing System Unit Assemblies](#)

FIREFLEX SYSTEMS INC

EX15538

1935 LIONEL BERTRAND
BOISBRIAND, QC J7H 1N8 CANADA

Special system water control valve and clean agent extinguishing system unit assembly, Model FireFlex DUAL consisting of Model PFC-4410RC Potter Electronic releasing control panel (or optional Notifier NFS-320 releasing control panel), E-1 or F-1 Viking single or double interlocked preaction assembly, and SEVO 3MTM NovecTM 1230 clean agent system unit in agent-charged capacities from 40-601 lbs (18-273 kg), super-pressurized to either 360 psig (25 bar) or 500 psig (34.5 bar).

A description of these extinguishing system units and the design and installation limitations are contained in the Listee's installation manuals FM-0860-0-4B and FM-0860-0-6B, dated June 2009, or manuals FM-0860-0-11D, FM-0860-0-12D, FM-0860-0-17B, FM-0860-0-18B, FM-0860-0-30A, or FM-0860-0-31A, dated November 2011. Copies are available from the above Listee.

[Last Updated](#) on 2012-05-03

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".